TEXAS UNIV AT AUSTIN DEFENSE RESEARCH LAB
QUARTERLY PROGRESS REPORT NUMBER 9, 1 AUGUST-31 OCTOBER 1968.(U)
DEC 68
ROBER-95181 AD-A069 139 UNCLASSIFIED NL AD A069139 END DATE FILMED 6-79

multary physics

UNCLASSIFIED

MOST Project

DEFENSE RESEARCH LABORATORY THE UNIVERSITY OF TEXAS AT AUSTIN

13 December 1968

Copy No. 1

QUARTERLY PROGRESS REPORT NO. 9 UNDER CONTRACT NObsr-95181 (U)

1 August -31 October 1968

NAVAL SHIP SYSTEMS COMMAND Contract NObsr-95181 Project Serial No. SF 1010316, Task 8614

690114-0295

FILE COPY, 300

0000 86

MOST Project

CONTRACTOR OF THE

(This page is UNCLASSIFIED.



Number

(12) 18p

13 Dec 68

QUARTERLY PROGRESS REPORT

1 August -31 October 1968 .

NAVAL SHIP SYSTEMS COMMAND Contract NObsr-95181

Project Serial No. SF 1010316, Task 8614

(15) NO bsr -95181

'Defense Research Laboratory' is the designation used in this report. On 1 October 1968 the title was changed to

Applied Research Laboratories.

ASSESSION for

OTTO White Section A

OCCUPANT OF THE SECTION ASSESSION AVAILABILITY CODES

DIST. AVAIL. and/or SPECIAL

DISTRIBUTION STATEMENT A

Approved for public release; Distribution Unlimited

DEFENSE RESEARCH LABORATORY
THE UNIVERSITY OF TEXAS AT AUSTIN
AUSTIN, TEXAS 78712

(The reverse of this page is blank.)

CONFIDENTIAL

UNCLASSIFIED 690114-0295

D D C

MAY SO 1979

LEGET VE

Donn ad Vi 3 Li Vilk;

TABLE OF CONTENTS

		Page
Ι.	INTRODUCTION	1
II.	CEPSTRUM ANALYSIS	3
III.	VOCODER ANALYSIS OF ACTIVE SONAR DATA	7
IV.	QUADRATURE CORRELATION	13
v.	REPORTS AND PUBLICATIONS	15

(This page is UNCLASSIFIED.)

I. INTRODUCTION

(U-recto) The efficiency in computing the Cepstrum of narrow band signals has been increased by the use of direct quadrature sampling of narrow band signals. As a practical application of Cepstrum to sonar, this is an important step. It means that a Cepstrum can be computed rapidly on a general purpose computer without the use of fast special purpose hardware. As soon as the programming is perfected, the new method will be used to analyze more real data. One of the purposes will be to test the ping-to-ping stability of selected submarine data.

(U-POUO) More work was done on a vocoder analysis of active sonar returns. This work has been interesting, but due to a lack of time it will have to be discontinued.

(U-POUS) A very efficient program to compute quadrature crosscorrelations based on the fast Fourier transform (FFT) was developed. A figure is presented showing its computational speed versus the number of lags computed (see Fig. 7).

(The reverse of this page is blank.)


II. CEPSTRUM ANALYSIS

(J. A. Shooter)


- (C) In Quarterly Progress Report No. 8 on Contract NObsr-95181 (U), it was shown that the power spectrum of a narrow band signal can be computed directly from the signal's quadrature components. The computation time thus saved was approximately a factor of 16. This technique has now been successfully applied to computing the Cepstrum of a narrow band signal. An illustration is shown in Fig. 1, the data in this case being a return from a stern aspect submarine. The transmitted signal was a linear FM sweep with a bandwidth W of 625 Hz, a time bandwidth product TW of 64, and a carrier frequency, f, of 5000 Hz. Each quadrature component was sampled at a rate of 2W. The power spectrum of the positive frequencies is shown in Fig. la. The frequency axis begins at $f = f_0$, and f increases to $f = f_0 + W$ at the center of the plot. Then f changes to $f = f_0$ - W and increases to f at the end of the frequency axis. This rather strange frequency axis is in keeping with the Cooley-Tukey version of the fast Fourier transform, and it is necessary to leave it in that order so that the next Fourier transformation will put the Cepstrum peaks in the correct position. This is not a symmetrical function.
- (U-rese) The next step in computing a Cepstrum is shown in Fig. 1b, which is a filtered logarithm of Fig. 1a. In this case, it was assumed that the log power was a time series sampled at 20 kHz. The filter was a recursive band-pass 1-pole Butterworth filter set at 350 to 6000 Hz. The filter frequency limits are related to the time delays between superimposed waveforms or target size. The upper and lower limits cover target sizes from stern to beam aspects. In addition, to remove ringing due to the filter, the first and last 10% of the filtered log power was smoothed to zero by half cosine bells.



(a) POWER SPECTRUM



(b) FILTERED LOG POWER



(c) QUADRATURE CEPSTRUM

FIGURE 1

COMPUTATION OF A CEPSTRUM IN QUADRATURE FOR STERN ASPECT SUBMARINE DATA (U)

ARL - UT AS - 68 - 1569 JAS - RFO

4

- (C) The last step shown in Fig. 1c is the square of the modulus of the Fourier transform of Fig. 1b. In addition, a Hanning window was applied to the real and imaginary components before squaring. This final result is the Cepstrum. For 512 quadrature components, each sampled at twice the bandwidth, the computation time for the Cepstrum was about 3 sec. This was using FORTRAN language on a Control Data Corporation 3200 computer. In machine language on an ordinary general purpose computer there should be no trouble in computing a Cepstrum in less than 1 sec. The quadrature Cepstrum is actually the envelope of the Cepstrum, and the results are interpreted in the following manner. The main peak is a correlation of a strong highlight midway between the stern and the sail with the highlight from the sail. The correlations between the highlights of stern and of the bow are very weak, and they are almost lost in the noise.
- (U-Feve) These results are quite encouraging. The next few experiments will determine the proper data lengths to prevent "wrap around" and to optimize the signal-to-noise ratios. Once the data lengths are settled, then a ping-to-ping stability test will be carried out to determine the suitability of Cepstrum as an aid in classification of submarine echoes.

III. VOCODER ANALYSIS OF ACTIVE SONAR DATA (J. A. Shooter and R. E. Senterfitt)

- (U-Pete) In QPR No. 8 on Contract NObsr-95181 (U), an effort was made to display an FM return on a time vs frequency plot. The results at that time were puzzling. It is now known that the difficulty was in the fact that the overlapping FM waveforms can interfere to produce peaks in the plots. This is demonstrated in Fig. 2, which shows a vocoder plot of four closely spaced overlapping waveforms. In these, artificial data are used and each of the waveforms is identical. It is seen that the output of each filter is unique, and therefore the peaks should not be interpreted as highlight structure.
- (U-Fett) This is not to say that a time-frequency plot could not be useful. Figures 3, 4, 5, and 6 show vocoder plots of a bow aspect submarine. These represent four consecutive pings, and the results are consistent. At this time, the peaks have no meaning, other than to say that the target is complex. The high frequency ripple super-imposed on the large peaks are caused by frequency leakage through a rather poor filter, and they have no meanings.
- (U-1990) This could be an interesting problem as related to echo classification, but time does not allow its perusal.




FIGURE 2
VOCODER ANALYSIS OF ARTIFICIAL DATA
TW = 64 W = 625 Hz f₀ = 5000 Hz

8

UNCLASSIFIED

ARL - UT AS-68-1570 JAS-RFO 12-2-68




FIGURE 3

VOCODER ANALYSIS OF

BOW ASPECT SUBMARINE DATA (U)

TW = 64 W = 625 Hz f₀ = 5000 Hz

SEQUENCE 13 TAPE 244

ARL - UT AS-68-1571 JAS-RFO 12-2-68

9




FIGURE 4

VOCODER ANALYSIS OF

BOW ASPECT SUBMARINE DATA (U)

TW = 64 W = 625 Hz f₀ = 5000 Hz

SEQUENCE 14 TAPE 244

10

CONFIDENTIAL

ARL - UT AS-68-1572 JAS - RFO 12 - 2 - 68




FIGURE 5

VOCODER ANALYSIS OF

BOW ASPECT SUBMARINE DATA (U)

TW = 64 W = 625 Hz f₀ = 5000 Hz

SEQUENCE 15 TAPE 244

ARL - UT AS-68-1573 JAS - RFO 12 - 2 - 68





FIGURE 6
VOCODER ANALYSIS OF
BOW ASPECT SUBMARINE DATA (U)
TW = 64 W = 625 Hz f₀ = 5000 Hz
SEQUENCE 17 TAPE 244

IV. QUADRATURE CORRELATION

(J. A. Shooter)

(U-1000) Early in this quarter a computer program was developed to compute a quadrature crosscorrelation, based on the fast Fourier transform (FFT). To check the program, a comparison was made on identical sets of data using the FFT version and a program developed by the Signal Physics Division. The results were identical, and they are shown in Fig. 6 of QPR No. 3 on Contract NCXC4-68-C-1149 (U). Unfortunately, the FFT version was embarrassingly slow. A new version has just been developed that takes advantage of the symmetrical properties of the Fourier transformations of real numbers. The new version (FQFT) is now operational, and Fig. 7 shows the comparative computational times. The FFT program must compute data in blocks of powers of two, which accounts for the stairstep function shown in the figure. The two curves showing computational time intersect 5 times, and potential users will have to refer to Fig. 7 to decide which program to use for economy of time. The FFT program is written in FORTRAN and does floating point arithmetic, so that it can still be improved.



14

UNCLASSIFIED YOU ASSISTED

V. REPORTS AND PUBLICATIONS

(J. A. Shooter)

(U FOUC) The joint paper on narrow band signal processing by
Messrs. O. D. Grace and J. A. Shooter has yet to be written.
Miss C. J. Webb is now putting the finishing touches on a report
dealing with the practical aspects of time series analysis and the
FFT algorithm.

(The reverse of this page is blank.)
UNCLASSIFIED

(This page is UNCLASSIFIED.) FOR STRICEL OF ONLY

13 December 1968

DISTRIBUTION LIST FOR
QUARTERLY PROGRESS REPORT NO. 9
UNDER CONTRACT NObsr-95181 (U)
Project Serial No. SF 1010316, Task 8614
1 August - 31 October 1968
CONFIDENTIAL, GROUP 4

Copy No. 1 - 2 Commander, Naval Ship Systems Command Department of the Navy

Washington, D. C. 20360

Attn: SHIPS OOVIC

- Commander
 Naval Undersea Warfare Center
 San Diego Division
 271 Catalina Blvd.
 San Diego, California 92152
 Attn: Code S3180
 - Commanding Officer and Director
 U. S. Navy Underwater Sound Laboratory
 Fort Trumbull
 New London, Connecticut 06320
 Attn: Code 2242
 - Director
 U. S. Naval Personnel Research Activity
 Department of the Navy
 San Diego, California 92152
 - 7 Office of Naval Research Resident Representative The University of Texas at Austin 2507 Main Building Austin, Texas 78712
 - 8 Computer Science Division, DRL/UT
 - 9 Hydroacoustics Division, DRL/UT
 - 10 Signal Physics Division, DRL/UT
 - 11 Sonar Research Division, DRL/UT

(This page is UNCLASSIFIED.)

Distribution List for QPR No. 9 under Contract NObsr-95181 (Cont'd)

Copy No.

12	K. J. Diercks, DRL/UT
13	R. K. Goodnow, DRL/UT
14	L. A. Jeffress, DRL/UT
15	S. P. Pitt, DRL/UT
16	J. A. Shooter, DRL/UT
17	R. H. Wallace, DRL/UT
18	Library, DRL/UT

DEFENSE RESEARCH LABORATORY THE UNIVERSITY OF TEXAS AT AUSTIN





UNCLASSIFIED